

# PRE-COAT FILTER USAGE GUIDE

Filter Mfg. Model No.	*Effective Filtration Area (SQ. FT. UP TO)	◆ Amount of PURIFIBER®
Crystal Clear 42-050 Jacuzzi AV-40 Purex NSP24, FNSP24 Hayward EC-30, EC-40, DE2400 Pac Fab FNS-24 Am. Prod. Titan 570-230 Hayward RG450A, RG700A Waterway Clearwater FD090	24	15 oz.
Crystal Clear 42-052 Jacuzzi AV-60, AV-80 Purex NSP36, FNSP36 Sta-Rite DEPB-36 Waterway Crystal Water 570-0036 Pac Fab FNS-36 Am. Prod. Titan 570-240 Hayward EC-50, EC-65, DE3600 Sta-Rite PLD-70	36	22 oz.
Crystal Clear 42-054 Jacuzzi AV-100, EW-75 Purex NSP48, FNSP48 Sta-Rite S7D75 Waterway Crystal Water 570-0048 Pac Fab FNS-48 Am. Prod. Titan 570-250 Hayward EC-75, DE4800 Sta-Rite PLD-50	48	22 oz.
Crystal Clear 42-056 Jacuzzi EW-100, EW-125 Purex NSP60, FNSP60 Sta-Rite S8D110 Waterway Crystal Water 570-0060 Pac Fab FNS-60 Am. Prod. Titan 570-260 Hayward DE-6000 Sta-Rite DEPB51	60	36 oz.
Crystal Clear 42-058 Jacuzzi EW-150 Hayward DE720S Purex NSP72	72	44 oz.

\*See pool filter equipment label or service manual for the filter area of your pool filter system

◆ **NOTE:** 6 oz. per 10 sq. ft. recommended dosing rate for average bather load

**Use of clarifiers, coagulants and sequestrant agents is enhanced when used in conjunction with Purifiber®. Always thoroughly clean filter prior to converting from D.E. to Purifiber®. Additional filter backwashes may be required upon initial use, depending on condition of water.**

## INSTRUCTIONS

### Pre-Coat Filters

After all exhausted filter media has been backwashed from the filter, slowly pour the appropriate amount of Purifiber into the skimmer while circulation system is operating. NOTE: Slight agitation of Purifiber is suggested when adding to skimmer box.

### Cartridge Filters

To enhance cartridge filter performance and aid in cleaning, add up to 4 oz (2 cups) of Purifiber per 25 square feet of cartridge filtering area. Only add if cartridge is clean and free of oil and dirt. Clean cartridge if necessary by soaking in an appropriate cleaning solution. After pool water clarify is achieved, remove dirty cartridge and clean again to remove all dirt, debris and exhausted Purifiber. Use on a continuous basis to protect cartridge and assist in cleaning.

### Sand Filters

To enhance pool clarity with a sand filter, add 4 oz. (2 cups) of Purifiber for every 50 lbs. of sand contained in the filter. Reduce flow. Allow pump to circulate to achieve several pool water turnovers or until water clarity is achieved. After water is clear and/or the sand filter backwash is indicated, back flow the sand filter to remove dirt, debris and dirty Purifiber.